




Specifications

MODELS	GR™-15		GR™-20	
	Metric	US	Metric	US
Working height*	6.47 m	20 ft 8 in	8.07 m	25 ft 11 in
Platform height	4.47 m	14 ft 8 in	6.07 m	19 ft 11 in
A B Platform dimensions (length x width)				
Standard	0.89 x 0.75 m	35 x 29.5 in	0.89 x 0.75 m	35 x 29.5 in
Standard with extension	1.40 x 0.75 m	55 x 29.5 in	1.40 x 0.75 m	55 x 29.5 in
Stock picker	0.89 x 0.73 m	35 x 28.75 in	0.89 x 0.73 m	35 x 28.75 in
Stock picker w/adjustable tray	1.40 x 0.73 m	56 x 28.75 in	1.40 x 0.73 m	56 x 28.75 in
Standard AWP****	0.69 x 0.66 m	27 x 26 in	0.69 x 0.66 m	27 x 26 in
Narrow AWP****	0.66 x 0.51 m	26 x 20 in	0.66 x 0.51 m	26 x 20 in
C Height - stowed	1.57 m	5 ft 2 in	1.98 m	6 ft 6 in
D Length - stowed	1.35 m	4 ft 5 in	1.35 m	4 ft 5 in
E Width	0.75 m	2 ft 5.5 in	0.80 m	2 ft 7.5 in
F Ground clearance - centre	0.06 m	2.5 in	0.06 m	2.5 in



PRODUCTIVITY

Lift capacity	227 kg	500 lbs	159 kg	350 lbs
Lift capacity - extension deck	113 kg	250 lbs	113 kg	250 lbs
Drive speed - stowed	4.0 km/h	2.5 mph	4.0 km/h	2.5 mph
Drive speed - raised	0.8 km/h	0.5 mph	0.8 km/h	0.5 mph
Gradeability**	30%	30%	30%	30%
Turning radius - inside	zero	zero	zero	zero
- outside	1.42 m	4 ft 7 in	1.42 m	4 ft 7 in
Raise / lower speed	21 / 19 sec	21 / 19 sec	24 / 21 sec	24 / 21 sec
Controls	24 V DC proportional		24 V DC proportional	
Tyres - solid non-marking	25 x 8 x 20 cm	10 x 3 x 8 in	25 x 8 x 20 cm	10 x 3 x 8 in

POWER

Power source	24 V (four 6 V 225 Ah batteries)		24 V (four 6 V 225 Ah batteries)	
Hydraulic system capacity	8.33 L	2.2 gal	8.33 L	2.2 gal

WEIGHT***

	975 kg	2,149 lbs	1,112 kg	2,451 lbs
--	--------	-----------	----------	-----------

STANDARDS COMPLIANCE

ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Gradeability applies to driving on slopes. See operator's manual for details regarding slope rating.

*** Weight will vary depending on options and/or country standards.

**** Not available for CE

Features

STANDARD FEATURES

MEASUREMENTS

GR™-15

- 6.47 m (20 ft 8 in) working height
- 4.47 m (14 ft 8 in) platform height
- Up to 227 kg (500 lbs) lift capacity

GR™-20

- 8.07 m (25 ft 11 in) working height
- 6.07 m (19 ft 11 in) platform height
- Up to 159 kg (350 lbs) lift capacity

PRODUCTIVITY

- Extension platform with sliding midrail
- Work station tray (GR-15 only)
- Auxiliary platform lowering
- Low 0.39 m (15.5 in) platform entry height
- Patented rigid mast system
- Compact base 0.75 m x 1.35 m (29.5 x 53 in) (GR-15 only)
- Ground clearance 0.06 m (2.5 in) (stowed)
- Fully proportional lift and drive controls
- Battery charge indicator
- Onboard diagnostic system
- Tilt alarm
- Zero inside turning radius
- Dual wheel brakes
- Hydraulic brake release
- Pothole protection
- Hinged rear ABS covers for easy access to all major electrical and hydraulic components
- Tie down attachment points
- Overhead crane attachment point
- Large forklift pockets access
- Non-marking solid tyres
- Dual flashing beacons
- Motion alarm
- Automotive horn
- Descent alarm

POWER

- Automatic 25 amp battery charger
- 24 V (four 6 V 225 Ah batteries)

OPTIONS & ACCESSORIES

PRODUCTIVITY

- 0.51 m (20 in) extension platform with sliding midrail
- 0.51 m (20 in) extension platform with gate
- Stockpicker platform with dual side entry gates and adjustable tray
- Stock picker rear parcel tray (GR-15 only)
- Fluorescent tube caddy
- Stockpicker platform with dual side entry gates and adjustable tray

POWER OPTIONS

- 240 V power to platform
- Maintenance-free batteries



Genie Australia – Toll free number 1800 788 633

Brisbane (Head Office)
33 Kimberley Street
Darra QLD 4076

Sydney
74 Glendenning Road
Glendenning NSW 2761

Melbourne
374 Hammond Road
Dandenong VIC 3175

Perth
83 Bannister Road
Canning Vale WA 6155

Genie United States Distributed by:

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington
98073-9730

Effective Date: April, 2009. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie is a Registered Trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Company. © 2009 Terex Corporation.